



Product specifications can be found on page 2.



FIELD MODIFIABLE WALL STRUCTURE PACKAGE

PKG500

REVISED 8/1/18

Field Modifiable Wall Mounted Structure Packages

Entire wall mount package shall consist of one each of the following components.

Structure shall be constructed of 100% welded 2" diameter DOM seamless tubing with a 10 ga. wall thickness.

1 5/8" diameter extension tubes shall fit inside the 2" tubes to allow a minimum of 12" adjustment to a maximum of 48" adjustment (PKG500). Adjustment shall allow the face of the backboard to be anywhere between 12" and 48" from the wall. Telescoping tubes shall be cut and triple set screwed, then drilled and bolted in place, at desired extension length at final assembly. All mounting brackets and hinge components shall be a minimum of 7 ga. thick and all bolts at the pivot location shall be no less than 5/8" diameter grade 5 zinc plated. All steel components shall be finished with a gray powder coated finish. Steel structure shall mount to 2" x 8" southern yellow pine wall struts that shall be attached directly to the wall with fasteners selected by the installer. 800#, 3/16" proof coil chain shall extend at an approximate angle of 45° to brackets attached to a third 2" x 8" wall strut. Chain shall be tensioned by means of a turnbuckle. Wall mount structure shall have a lifetime limited warranty.

Backboard shall be 42" x 54" and constructed of 1/2" thick tempered glass with an official white shooter's square and border and shall have 5" x 4" goal mounting pattern. Frame shall be aluminum extrusion held together in the top corners by means of 7 ga. steel corner brackets that provide for the industry standard 36" x 62" short board corner mounting pattern. A fabricated steel rim support structure shall extend the full 54" width of the bottom of the backboard and be mounted to the aluminum framework in no less than 10 places. Steel spacers shall protrude through large holes in the glass for rim mounting. At no time shall the rim be allowed to contact the glass at any point during play when up to 1,000 lbs. of pressure is applied to the rim. Backboard shall meet all NCAA and National High School Federation standards and carry an unconditional lifetime warranty. Frame shall be predrilled to allow mounting of Bison Model BA68U DuraSkin Backboard padding. Board shall weigh 200#.

Goal shall be constructed using 5/8" diameter high strength AISI 1018 cold drawn carbon steel ring with continuous wire netlocks to accept anti-whip nylon net (included). All backplate components shall be constructed of 3/16" thick steel.

The mounting plate shall be punched with hole patterns for mounting to 42" x 54" rectangular backboards.

The rim support brace shall be 1/4" x 1 1/2" steel and provide continuous support for 180° of the circumference of the 5/8" ring. The breakaway mechanism shall be of the positive lock design, factory preset. An automatic return shall be provided by means of two return springs which shall also cushion the breakaway action when the pressure release setting has been exceeded. Two hardened steel balls shall be contained in a tubular assembly with each being forced outward with equal pressure by a single spring. The balls shall nest on each side of the rim/backplate assembly in a hardened detent. Said ball/detent mechanism shall provide proper breakaway pressure. All pinch points shall be eliminated for player safety. Entire mechanism shall be covered by a steel coverplate. All components shall be coated with an official orange powder coated finish. Goal shall carry an unconditional 3-year replacement warranty, be manufactured in the USA and meet all NCAA and National High School Federation standards and weighs 22#.

Padding shall be molded to meet or exceed all standards set forth by the NCAA, National High School Federation and FIBA. Padding shall be cellular construction with a skin of an average minimum thickness of 1.5mm. The skin shall be produced integral to the cushion using a self-skinning molding process. The tear strength of the skin shall be a minimum 125 psi. The padding system shall be capable of mounting to all brands and styles of 54" rectangular backboards by means of eight bolts (provided). A steel track molded into the padding shall provide rigidity and strength to the mounting system. The corners of the padding shall be molded square for maximum safety and shall not require mitering, gluing or forming for attachment. All hardware shall be provided. The two section padding system shall be available in official Gray, Royal, Navy, Columbia Blue, Scarlet, Orange, Gold, Kelly Green, Forest Green, Black, Maroon, Purple, Vegas Gold, Cardinal, Brown, Burnt Orange and Pink. Colors shall be continuous throughout the thickness of the padding, not only on the skin. The warranty shall extend for 10-years and cover tearing and deterioration, as well as detachment from the backboards and weigh 12#. Entire system shall weigh approximately 470#. Installation to be completed in accordance with manufacturer's instruction. Do not scale drawings.



FIELD MODIFIABLE WALL STRUCTURE PACKAGES

PKG500

REVISED 8/1/18